



GE



Surface	Fine structure matt (standard), silk gloss, matt Powder-coated 200 °C before assembly
Colours	RAL Classic, RAL Design, NCS, VSR
Finishes	Wood, stone, rust
Pretreatment	Ocean Line Plus possible
Notes	Electric drive and finish are not possible in combination with special shapes When shutter closures are used (art. no. 5315/5316) supports are required (art. no. 5323) Upper corner connections are additionally secured by aluminium nails With special shapes a different support frame is used for the insert for technical reasons Rod locks cannot be exchanged Floor locking in combination with special shapes can only be installed to a limited extent Drain holes at bottom of frame





Min./Max. dimensions	Width: 280 to 800 mm Height: 800 to 2500 mm
Weight	Approx. 10 kg/m ²
Frame profile	75 × 32 mm extruded aluminium hollow chamber profile
Centre	73 × 10 mm extruded aluminium hollow chamber profile
Horizontal cross-panel	60 × 32 mm extruded aluminium hollow chamber profile
Stop bead	Supplied loose, black or white rubber (depending on sash colour)
Corner connections	Aluminium bracket, glued-in and additionally secured by plastic pins
Options	Notching Floor locking Opener Add-on lock Easyflex Electric drive Rabbet bead Vertical cross-panel Segmental arch, hollow (mounted) Horizontal cross-panel Segmental arch, solid (mounted) Frames Half-round arch (mounted) Rod lock Special shapes (arched frame profile) Pre-installation Basic frame Catch