



MS-ROM



Surface	Fine structure matt (standard), silk gloss, matt Powder-coated 200°C before assembly
Colours	RAL Classic, RAL Design, NCS, VSR
Finishes	Wood, stone, rust
Pretreatment	Ocean Line Plus possible
Notes	Electric drive and finish are not possible in combination with special shapes When shutter closures are used (art. no. 5315/5316) supports are required (art. no. 5323) Inserts are exchangeable Distribution of horizontal cross-panel: 1/3 top, 2/3 bottom; division by dimensions specification also possible (depending on distribution of slats) Drain holes at bottom of frame Floor locking in combination with special shapes can only be installed to a limited extent



Min./Max. dimensions Width: 280 to 800 mm
 Height: 800 to 2500 mm

Min./max. infeed 46,0–51,5 mm
Inclination angle 15°
Weight Approx. 7 kg/m²

Frame profile 75 × 32 mm extruded aluminium hollow chamber profile
Slat profile 54 × 10 mm extruded aluminium hollow chamber profile
Slat carrier profile 32 × 11 mm extruded aluminium profile
Horizontal cross-panel profile 60 × 32 mm extruded aluminium hollow chamber profile
Centre Polystyrene rigid foam board with double-sided aluminium sheeting
Stop bead Supplied loose, black or white rubber (depending on sash colour)

Corner connections Aluminium bracket, glued-in and additionally secured by plastic pins

Options Notching | Add-on lock | Opener | Floor locking | Electric drive | Easyflex |
 Rabbet bead | Vertical cross-panel | Half-round arch (mounted) | Horizontal cross-panel | Inside opener crank |
 Frames | Basic frame | Rod lock | Segmental arch, hollow (mounted) | Pre-installation |
 Segmental arch, solid (mounted) | Catch | Special shapes (arched frame profile)